

安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co., Ltd.

安徽省蚌埠市高新区兴中路985号日月 科技园 电话:0086-552-3827158

传真:0086-552-3822922

Sunmoon industry park, 985 Xingzhong Road,Bengbu, China 233000

> Tel: 0086-552-3827158 Fax: 0086-552-3822922

Modified organosilicon defoamer XPJ-100

1. XPJ-100 series organosilicon defoamer is processed with a variety of special emulsifiers produced by our company. The product is not only fast in defoaming and easy to disperse, but also solves the shortcomings of easily broken emulsion and bleached oil after dilution. At the same time, its antifoaming performance is greatly improved.

XPJ-100 series can be divided into five types according to the solid content: XPJ-110, XPJ-115, XPJ-118, XPJ-120 and XPJ-130. The operating temperature can reach 100 °C, which is a kind of general defoamer with low price and good quality.

2. Typical characteristics Milky white appearance Emulsion ionic non ionic type PH 7-9

Emulsion stability centrifuge test, 3000 rpm / min, 20 minutes, no stratification, no precipitation.

3, use

(1) used for defoaming in textile printing and dyeing process and defoaming in textile printing and dyeing auxiliaries

(2) to eliminate harmful foam in water treatment, industrial circulating water, paper washing, chemical cleaning, chemical fertilizer, caking agent and petrochemical industry.

(3) to remove harmful foam in drilling mud and cementing cement for oil exploitation.

(4) elimination of other aqueous phase froth.

4, packaging

Our company adopts 25kg, 50kg, 200kg plastic buckets and 200kg inner coated iron buckets for packaging

5. Storage and transportation

It is suitable for room temperature storage, not near the heat source, not exposed to the sun, not adding acid, alkali, salt and other substances in the defoamer. It can't be stored for a long



安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co., Ltd.

安徽省蚌埠市高新区兴中路985号日月

科技园

电话:0086-552-3827158 传真:0086-552-3822922 Sunmoon industry park, 985 Xingzhong Road,Bengbu, China 233000

> Tel: 0086-552-3827158 Fax: 0086-552-3822922

time after being diluted with water and won't be layered within one year of storage. If there is layered demulsification beyond this period, it can be stirred evenly before use without affecting the use effect and transported as non dangerous goods.

6, use

Before using the product in batches, the customer shall carefully read the product manual and conduct necessary defoaming test to ensure the safety of use. If you have any questions about the products, please contact us and our company will serve you wholeheartedly. This material is based on our current knowledge and experience. Therefore, this material shall not be used to replace any test required by you when you use our products on a large scale or in a batch to fully meet your characteristics. For the loss caused by the product does not meet the sales quality index, the company only undertakes to return the payment or replace the product. Our suggestions for application or use are for reference only.