



安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co.,Ltd.

安徽省蚌埠市高新区兴中路985号日月科技园

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

电话：0086-552-3827158

Tel: 0086-552-3827158

传真：0086-552-3822922

Fax: 0086-552-3822922

Organic defoamer XPJ-7533

1. Typical product data

Appearance: white viscous emulsion

Density (g / cm³ 25 °C) about 0.97

Viscosity (MPa. S. 25 °C) 12500-6000 MPa. S

Active content 100%

Flash point ≥ 315 °C

Storage period 12 months

2. Product introduction

Xpj-7533 type organic defoamer is an organic compound with polysiloxane as the main material. It can be dispersed in low molecular weight and low viscosity petrochemical products as particles.

It can quickly eliminate the bubbles produced in the process of crude oil exploitation, gathering and transportation, refining and processing, oil residue storage and delayed coking. It can withstand the high temperature of about 400 °C without being damaged. It is an assistant in the process of petrochemical production and processing.

3. Application field

It can be used for defoaming in the process of oil exploitation, processing and refining of petroleum products and delayed coking.

XPJ-7533 is very effective in preventing foam formation, so it is better to add foam material before foaming, so that it can be more economical and effective in preventing foam formation.

4. Usage

When xpj-7533 defoamer is used, it is better to dilute the defoamer with process solution first, and then add the mixture into the foaming solution, so that the defoamer can be quickly dispersed into the foaming solution to play a better defoamer effect. The recommended concentration is 10-100ppm.

5, packaging

Our company adopts 25kg, 50kg, 200kg plastic buckets and 200kg inner coated iron buckets for packaging

Add: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158 Fax: 86-552-3822922 Website: www.siliconeoil.cn or www.siliconeoil.net



安徽艾约塔硅油有限公司

Iota Silicone Oil(Anhui) Co.,Ltd.

安徽省蚌埠市高新区兴中路985号日月科技园

Sunmoon industry park, 985 Xingzhong Road,Bengbu, China 233000

电话：0086-552-3827158

Tel: 0086-552-3827158

传真：0086-552-3822922

Fax: 0086-552-3822922

6. Storage and transportation

It is suitable for room temperature storage, not near the heat source, not exposed to the sun, not adding acid, alkali, salt and other substances in the defoamer. It can't be stored for a long time after being diluted with water and won't be layered within one year of storage. If there is layered demulsification beyond this period, it can be stirred evenly before use without affecting the use effect and transported as non dangerous goods.

7. Use safety

Before using the product in batches, the customer shall carefully read the product manual and conduct necessary defoaming test to ensure the safety of use. If you have any questions about the products, please contact us and our company will serve you wholeheartedly.

This material is based on our current knowledge and experience. Therefore, this material shall not be used to replace any test required by you when you use our products on a large scale or in a batch to fully meet your characteristics. For the loss caused by the product does not meet the sales quality index, the company only undertakes to return the payment or replace the product. Our suggestions for application or use are for reference only.